
# IS5111si, IS5116si, IS5121si

## Fitting Instructions: Silicone Rubber Fin Seals



Architectural Door Seals



#### Description of contents

- Aluminium carrier (1)
- Silicone Rubber Fin (2)
- Self-adhesive tape (3)
- Bag of screws
- Fitting instructions

#### Tools required for installation

- Tape measure
- Saw (power or hand)
- Screw driver
- Knife
- Drill (power or hand)
- 2.5mm drill bit
- 4.0mm drill bit
- Pencil or Marker

## Other Integrity™ Architectural Seals include:

- Door Perimeter Seals
- Door Bottom Seals
- Automatic Door Bottom Seals
- Threshold Plates
- Brush Seals
- Magnetic Seals

Contact your nearest Kilargo office for further details.

# Installation detail: Silicone rubber blade seal

It is not necessary to remove the door unless otherwise specified.

| Step 1 | Remove the seal from the packaging and measure the length of the door/frame member to |
|--------|---|
| -      | which the seal is the be fitted. (Refer installation details).                        |

- **Step 2** Pull back the silicone gasket and cut the aluminium carrier to the required length. Slide silicone gasket back into position and cut to length using a sharp knife.
- **Step 3** Screw fixing: Using a power drill with a 4.0mm drill bit, create fixing holes in the aluminium carrier at the required positions.
- **Step 4** Remove the backing from the self-adhesive tape and position the seal.
- **Step 5** Close the door and check for a uniform seal.
- **Step 6** Drill pilot holes with a 2.5mm drill bit (if required).
- Screw-fix into position with the screws supplied.

  In many situations the self-adhesive tape may be sufficient to hold the seal in place, provided the surface is clean, smooth and dry. For added security, it is recommended to use the screw fixings.

## **Important**

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to ensure the door assembly to which it is fitted, closes and latches properly.

#### Note


Recommendations as to methods for use of materials and construction details are based on the experience and knowledge of Kilargo and are given in good faith as a general guide and service to designers, contractors and manufacturers. Kilargo reserves the right to make alterations or delete any installation detail without prior notice.



Door Bottom Installation Detail



Meeting Stile Installation Detail



Perimeter Installation Detail

Literature Code: IS5111si/16si/21si 05/12

