



Intumescent Mastic

PERIMETER SEALING

Kilargo Intumescent Mastic is designed for fire damper perimeter sealing. It is specially formulated for adhesion to metal, plastic, concrete, masonry and plasterboard materials.

Kilargo Intumescent Mastic is water based for easy clean up, and offering smooth gunnability, Kilargo Mastic is flexible, paintable and has acoustic properties. Kilargo approvals specify the use of Kilargo Intumescent Mastic.

How to Order

310 ml CARTRIDGE KIM-310 GREY

Supplied in 310 ml tubes individually or in

carton quantity.



For more product information please scan QR code or visit: www.kilargo.com.au

Suggested Specification

The Intumescent Mastic shall be Kilargo water based type, supplied in 310 ml cartridges.

Mastic shall be Kilargo Intumescent type to conform with the Kilargo approved methods of installation.

Avaliability

Supplied in 310ml cartridges. Grey colour standard.

Methods of Use

- Surfaces should be free from oil
- 2. Apply mastic to both sides of perimeter gaps to a depth of at least that of the gap width.
- 3. The surface will be tack free in approximately 20 minutes in dry conditions or about 2 hours in a humid environment.
- 4. Large joints (not exceeding 25 mm) can be built up with additional applications after initial drying, in order to avoid excessive slump. It may also be necessary to use a non-combustible material or backing rod in such applications.
- Any tools can be cleaned with water.

Kilargo Pty Ltd

15 Wentworth Place Banyo QLD 4014

T: 1300 858 010 info@kilargo.com.au www.kilargo.com.au