

IS8110si



A fully-mortised, automatic "flat back" seal to suit installation to aluminium door rails for single action doors. It operates automatically by a spring loaded mechanism which lifts the seal clear of the floor as soon as the door is opened by a few millimetres. The seal operates automatically by pressure against the door jamb on its adjustable strike button.

Standard lengths

- 610mm
- 820mm
- 920mm
- 1070mm
- 1220mm

IS8110si maximum allowable cut-back sizes

- 610mm seal cut to 580mm
- 820mm seal cuts to 610mm
- 920mm seal cuts to 820mm
- 1070mm seal cuts to 920mm
- 1220mm seal cuts to 1070mm

(*Seals can be cut on site for exact dimension)

Standard colours



- Silver anodised aluminium with grey silicone rubber compression gaskets

Approval/s

- Certifications GVV1.R26629, GVWZ.R26629, GVWZ7.R26629
- Conforms with BCA Specification C3.4 smoke sealing requirements
- Acoustically tested in accordance with AS1191, ISO140.3 and ISO10140-2
- Durability tests demonstrating over 1,000,000 open and close cycles

Features

- Ambient (cold) temperature smoke control
- Medium temperature smoke containment
- Medium temperature smoke (200°C) containment
- Sound containment (acoustics)
- Energy efficient



IS8110si



All seals proudly manufactured in Australia